



TITAN Supersyn SAE 10W-60

Ultra high-performance oil for passenger cars. Good cold starting behaviour and low oil consumption. Highly durable lubricating film and high oil pressure.

Description

TITAN Supersyn 10W-60 is the high-viscosity engine oil of the TITAN Supersyn-range. It is based on innovative engine oil technology. The modern and reliable additive technology secures reliable performance at all operating conditions. This up to date Ultra High Performance Engine Oil can be used all over the year. The good cold flow properties of TITAN Supersyn 10W-60 are providing fastest lubrication to all parts of the engine. Friction and wear will be effectively reduced due to a reliable oil film being generated. TITAN Supersyn 10W-60 guarantees engine durability and improved oil pressure under city cycle mode as well as under top speed racing conditions.

Application

TITAN Supersyn 10W-60 can be used for passenger cars and light duty vehicles with naturally aspirated or supercharged gasoline and diesel engines. Being an all season's motor oil, TITAN Supersyn 10W-60 offers good cold start and fuel economy in the winter as well as high thermal stability in summer. TITAN Supersyn 10W-60 is miscible and compatible with conventional branded engine oils. However, mixing with other engine oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to TITAN Supersyn 10W-60. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages/Benefits

- Multipurpose applicability in many vehicles
- Good cold start performance
- Very good engine cleanliness
- High thermal stability
- Low evaporation loss, low oil consumption
- Improved oil pressure even at high ambient temperatures
- Sustainable wear protection

Specifications

- -

Approvals

- -

FUCHS Recommendations

- ACEA A3/ B3
- API SL / CF
- FIAT 9.55535-H3



CHARACTERISTICS

Density at 15 °C	DIN 51757	0.850 g/ml
Colour	DIN ISO 2049	3.5 ASTM
Flash Point, CoC	DIN ISO 2592	230 °C
Dynamic Viscosity at - 25°C	DIN 51398	6,700 mPas
Kinematic Viscosity at 40°C	DIN 51562-1	173 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	23.5 mm ² /s

PI60409e, PMA, 17.12.2010, Page 2



The information contained in this product information is based on the experience and know-how of FUCHS EUROPE SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pretreatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS EUROPE SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS EUROPE SCHMIERSTOFFE GMBH.

© FUCHS EUROPE SCHMIERSTOFFE GMBH. All rights reserved.